

TYPE APPROVAL CERTIFICATE

Certificate no.:
TAP00001X8
Revision No:
2

This is to certify:
that the Butterfly Valves

with type designation(s)
Centric Resilient Seated BF Valves, type series: 50, 51, 52, 53 and 58

issued to
Delval Flow Controls Pvt. Ltd.
Satara, Maharashtra, India

is found to comply with
DNV rules for classification – Ships Pt.4 Ch.6 Piping systems
DNV class programme DNV-CP-0186 – Type approval – Valves

Application:

Products approved by this certificate are accepted for installation on all vessels classed by DNV.

Temperature range: see certificate
Max. working press.: PN 10, PN 16 and PN 20
Sizes: see certificate

Issued at **Hamburg** on **2025-02-10**

This Certificate is valid until **2030-02-09**.

DNV local unit: **Mumbai NB & CMC**

Approval Engineer: **Ana Cristina Do Carmo Insfran**

for **DNV**



Digitally Signed By:
Sven Klinger
Location: DNV Hamburg,
Germany

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Product description

Resilient Seated Butterfly Valve type series: 50, 51, 52, 53 and 58 for installation in piping systems.

Valve design: API 609 Category A, EN 593
 Valve side flanges: DIN EN 1092, ASME B 16.5 class 150, JIS B2220, ASME 16.47
 Valve top flange: EN ISO 5211

Butterfly valve design styles according to the following types:

Wafer type; Lug type; Double Flange type

Butterfly valve	Nominal sizes	Pressure ratings (depending on sizes)
Wafer type	DN 50 to DN 600 (2" to 24") DN 650 to DN 1000 ¹ (26" to 40")	PN 10 / PN 16 ²
Lug type	DN 50 to DN 600 (2" to 24")	PN 10 / PN 16 ²
Flanged type	DN 50 to DN 1200 ¹ (2" to 48")	PN 10 / PN 16 ² / PN 20

Design temperatures:

Temperature range (°C)	Seat type
-25°C to 100°C (-13°F to 212°F)	for NBR seated valves of all body material combination
-29°C to 140°C (-20°F to 284°F)	for EPDM seated valves with body material ductile iron and carbon steel
-35°C to 140°C (-31°F to 284°F)	for EPDM seated valves with body material Nickel Aluminum Bronze, Stainless Steel ²

Butterfly valves may be equipped with manual, pneumatic or electric actuator.³

Materials:

Valve parts	Material type	Standard
Body	Ductile Cast Iron Cast Copper Alloy Nickel Aluminium Bronze Cast Copper Alloy Carbon Steel Stainless Steel Duplex Stainless Steel	ASTM A395 (Gr.60-40-18) ; ASTM B148 Gr. C95800 NES 747 Part 2 BS 1400 Gr. LG4C ASTM A216 Gr.WCB; ASTM A351 Gr.CF8M/CF8 ASTM A995 Gr. 4A/5A/6A
Disc	Duplex Stainless Steel Ductile Cast Iron Stainless Steel Nickel Aluminium Bronze Cast Copper Alloy	ASTM A995 Gr. 4A/5A/6A ASTM A536 Gr.65-45-12 + Aroxy coated ; ASTM A536 Gr.65-45-12 + Nylon coated ASTM A351 Gr.CF8M/CF8 NES 747 Part 2 ASTM B148 Gr. C95800
Stem ⁴	Stainless steel Copper Alloy Bars	ASTM A479 type SS410; ASTM A564 type 630 (17-4PH); UNS S31803 (F51) ASTM A479 Gr.SS410-L2 NES 833 Part 2; Monel K400; Monel K500
Seat	EPDM, NBR-(BUNA-N)	

Notes:

¹ Applicable for General Assembly (Wafer) BFV bare stem (series 51 and 53)

² Not applicable for General Assembly (Wafer) BFV bare stem (series 51 and 53)

³ Actuators and additional mountings are not included in this type approval.

⁴ For nominal valve size 8" and above and for PN 16 ratings stem ASTM A564 type 630 (17-4PH) only applicable.

Application

Butterfly valves for control and shut-off applications

Operating media: Nonflammable gases, sea water, water, air, oil.⁵

Note⁵:

Fuel oil, lubrication oil, hydraulic oil and thermal oil are in this context regarded as "Flammable liquids".

See DNV Rules, Pt. 4, Ch. 1, Section 3 – Design principles

Limitation

Butterfly valves may not be used for flammable gases and applications with flowing media specified as dangerous and toxic fluids.

Valves fabricated of nodular cast iron of the ferritic type with specified elongation of 12% may be used on the following installations:

- Class II and Class III piping systems
- Ship's side and bottom and on the collision bulkead

Valves fabricated of grey cast iron and nodular cast iron with specified elongation of <12% are not permitted for the following installations and service conditions:

- Media having temperature below 0°C (32°F) and a temperature exceeding 120°C (248°F)
- Class I and II piping systems
- At the ship's side and bottom on sea chest and on collision bulkeads
- Valves under static head fitted on external wall of fuel oil tanks and tanks for other flammable liquids.

EPDM shall not be used for hydrocarbon service.

Body materials of copper, copper alloys and Al-Bronze are subjected to requirements according to DNV Rules Pt.2, Ch.2 – Metallic Materials, Section 10 and 11 and to operating temperatures limits specified in DNV Rules Pt.4, Ch.6 – Piping Systems, Section 2 – Materials.

Valves fabricated of copper and copper alloy shall not be used for media having temperature above the following limits:

- Copper and aluminium brass: 200°C (392°F)
- Copper nickel: 300°C (572°F)

Tests carried out / Production testing

The butterfly valves are subjected to the following scope of tests:

Test standard: EN 12266-1/API 598 DNV Pt.4, Ch.6 DNV CP-0186		
Title	Test reference	Purpose
Hydrostatic Pressure test	Valve body	To confirm the pressure containing capability of the shell against internal pressure Test pressure = 1,5 times the design pressure No leakage is permitted.
Hydrostatic / Pneumatic Seat tightness	Valve seat	To confirm the capability of the seat(s) to comply with the specified leakage rate, Leakage rate A - at the time of manufacture - In the direction(s) for which the valve is designed No visible leakage
Functional test	Valve assembly	Function test of complete assemble valve

Type Approval documentation

Renewal: TAP00001X8

Type Approval Assessment Report dated 2025-01-31

Letter statement no modification dated on 2025-01-31

Drawings No.:

PDBFV50560, PDBFV50570, PDBFV50730, PDBFV50740,
 PDBFV50750, PDBFV50760, PDBFV50850, PDBFV50860, PDBFV50870, PDBFV50880, PDBFV50890, PDBFV50900,
 PDBFV55070, PDBFV55080

PDBFV62060, PDBFV62070, PDBFV62080 dated on 2020-11-13.

Valve Test Certificates, diverse, dated on 2019-11-20 and for serie 58 dated on 2020-11-03

TA401_TA Assessment dated on 2019-11-24 and 2020-11-03

Test certificate dated on 2019-11-20

Test report witness dated on 2020-03-11

Quality Assurance Plan for the butterfly valve serie 58 dated on 2020-10-29

Certification

Application in machinery and piping systems.

Valves intended to be installed in piping system listed in DNV Rules Pt.4, Ch.6 – Section 1
 shall be certified according to DNV Rules Pt.4, Ch.6 – Piping systems, Section 9

Valve nominal size / Pressure rating

DN > 100 mm / PN > 16 bar

DN ≤ 100 mm / PN ≤ 16 bar

Ship side valves DN > 100 mm
 regardless of pressure rating

Type of Product Certificate (PC) / Issued by

PC Product Certificate / DNV

PD Product Declaration / Manufacturer

PC Product Certificate / DNV

Material certificates (valve bodies)

In accordance with DNV Rules Pt.4, Ch.6 – Piping systems, Section 2 – Table 3.

Marking of product

For traceability to this type approval the products are to be marked in particular with:

- Manufacturer's name or trade mark
- Valve type designation
- Size
- Maximum design pressure and temperature
- Arrow to indicate direction of flow

Place of manufacturing

Delval Flow Controls Pvt. Ltd.
Gat No. 25, Kavathe
Javale PO, Tal.Khandala,
Dist Satara PIN 412801,
Maharashtra State INDIA

Periodical assessment

For retention of the Type Approval, a DNV Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the Type Approval are complied with. Refer to DNV-CP-0338, Sec.4.

This certificate is only valid if required periodical assessments are carried out with satisfactory results.
To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

End of Certificate